NV60

Flammable DOT

NO HAPS

Strong Bonds

Fast Tack



NV60 is a high performance and versatile industrial strength contact adhesive. Water resistant, NV60 is designed for bonding a wide range of substrates to include fabrics, marine foam and upholstery, cork and insulation.

PRODUCT USAGE

NV60 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 2-4 minutes until tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance: Liquid, clear Specific Gravity: .74 + .03

Shear Adhesion: >100psi and >200°F

Spray Tip: ES6501 Spray Pattern: Web Spray

Flammability: Flammable per ASTM E-681-04

VOCs: <40% by wt (aerosols) <320 g/L (canisters)

<160g/L (bulk)

Shelf Life: 15 months

Freezing: Not damaged by freezing but return to room

temp before use.

PACKAGING

NV60-013C
NV60-009C
9 lbs Disposable Canister
NV60-030C
30 lbs Disposable Canister
NV60-140C
140 lbs Returnable Canister
NV60-280C
280 lbs Returnable Canister

NV60-005 5 gal Pail NV60-055 52 gal Drum

All available in Clear (C)

KEY FEATURES

- No HAPS, Low VOCs
- · Non-Chlorinated Solvent
- Strong Bond Performance
- Fast Tack
- · Water Resistant

Disclaimer of Warranty: Pionite expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Mfd. for: Pionite (855) 497-0700

See MSDS Data Sheet for Proper Handling and Safety Information